

SL1100 Series Pipe Offset Addendum

Table 5.1

HEIGHT OF CHIMNEY COMPONENTS		<i>in.</i>	<i>mm</i>
Chimney Stabilizer			
	SL11	4-3/4	121
Ceiling Firestops			
	FS538	0	0
	FS540	0	0
Offsets/Returns			
	SL1130	18	457
Roof Flashing			
	RF570	0	0
	RF571	0	0
Chimney Sections*			
	SL1106	4-3/4	121
	SL1112	10-3/4	273
	SL1118	16-3/4	425
	SL1136	34-3/4	883
	SL1148	46-3/4	1187

* Dimensions reflect effective height.

Table 5.2

A		B		SL1106	SL1112	SL1118	SL1124	SL1136	SL1148
<i>in.</i>	<i>mm</i>	<i>in.</i>	<i>mm</i>						
4-3/4	121	18	457	-	-	-	-	-	-
6-5/8	168	21-1/8	537	1	-	-	-	-	-
8-3/8	213	24-1/4	616	2	-	-	-	-	-
9-5/8	244	26-3/8	670	-	1	-	-	-	-
11-3/8	289	29-1/2	749	1	1	-	-	-	-
12-5/8	321	31-1/2	800	-	-	1	-	-	-
14-3/8	365	34-5/8	879	-	2	-	-	-	-
15-5/8	397	36-3/4	933	-	-	-	1	-	-
17-3/8	441	39-7/8	1013	1	-	-	1	-	-
20-3/8	517	45-1/8	1146	-	-	2	-	-	-
21-5/8	549	47-1/8	1197	-	-	-	-	1	-
23-3/8	594	50-1/4	1276	1	-	-	-	1	-
26-3/8	670	55-1/2	1410	-	-	-	2	-	-
27-5/8	702	57-1/2	1461	-	-	-	-	-	1
29-3/8	746	60-5/8	1540	1	-	-	-	-	1
32-3/8	822	65-7/8	1673	-	1	-	-	-	1
35-3/8	899	71	1803	-	-	1	-	-	1
38-3/8	975	76-1/4	1937	-	-	-	1	-	1
40-1/4	1022	79-3/8	2016	1	-	-	1	-	1
44-3/8	1127	86-5/8	2200	-	-	-	-	1	1
46-1/4	1175	89-3/4	2280	1	-	-	-	1	1
50-3/8	1280	97	2464	-	-	-	-	-	2

Proper assembly of air cooled chimney parts results in an overlap of chimney joints of 1-1/4 in. (32 mm). Effective length is built into this table.