



## The Best Warranty in the Industry

Selkirk Chimney & Venting Systems feature advanced engineering designs and premium materials which allow us to offer a Lifetime Warranty.

See written warranty for details.



### Complete Product Lines to Meet Your Market Needs!

#### HVAC Products

- Grilles**
- Registers**
- Diffusers**
- Chimney:**
  - Ultra-Temp
  - Ultra-Temp Large
  - Galva-Temp
  - Galva-Temp Large
  - SuperPro
  - SuperVent
- Venting:**
  - Direct-Temp / Gas
  - RV & R Type B Gas Vent
  - Flexi-Liner
  - Versa-Liner
  - Saf-T Vent Special Gas Vent
  - Polyflue
  - Heatfab
- Filters**
- Sheet Metal Duct Components**
- Access Doors**

#### Hearth Products

- Chimney:**
  - Ultra-Temp
  - Ultra-Temp Large
  - Galva-Temp
  - Galva-Temp Large
  - SuperPro
- Venting:**
  - Direct-Temp / Gas
  - Direct-Temp / Pellet
  - Direct-Temp / Multi-Fuel
  - Double Wall Stove Pipe
  - Saf-T Pipe
  - UPP Pellet Pipe
  - VP Pellet Pipe
  - Flexi-Liner
  - Versa-Liner
  - Saf-T Liner



Reduce, Reuse, Recycle  
Our literature is printed on recyclable paper



RESIDENTIAL AND COMMERCIAL: VENT | CHIMNEY | GRILLES | REGISTERS | DIFFUSERS

United States  
5030 Corporate Exchange Blvd.  
Grand Rapids, MI 49512

1.800.992.VENT (8368)  
info@selkirkcorp.com



selkirkcorp.com

Canada  
375 Green Road  
Stoney Creek, ON L8E 4A5

1.888.SELKIRK (735.5475)  
cscanada@selkirkcorp.com

## PRODUCT APPLICATION GUIDE



Selkirk Corporation manufactures a complete line of exhaust and venting pipe products for most any residential or commercial application. This chart serves as a general specification reference and selection guide to the residential and light commercial products. For information regarding our commercial line of products, visit us at [www.selkirkcommercial.com](http://www.selkirkcommercial.com).





# APPLICATION GUIDE

**YOUR PRODUCT SELECTION IS GOVERNED BY FOUR MAJOR CONSIDERATIONS:**

1) Type of heating appliance

2) Fuel(s) to be burned and vapors or gases to be removed

3) Operating temperatures of the appliance

4) Building use and type of construction materials used

APPLICATIONS																		
Uses	Multi-Fueled Appliances	Direct Vent System	Gas Appliance Connector, Manifolding, Venting & Common Vent				Gas Vent Connector		Chimney Liner		Chimney						Connector between Appliance & Chimney	Pellet Fueled Appliances
Fuels or Vapors	Bio-Pellets, Corn	Natural Gas, Propane, L.P.Gas	Natural Gas, Propane, or L.P. Gas Only						All Residential Fuels; Gas, Liquid, & Solids									Pellets, Gas and Oil
Operating Conditions	Direct Vent	Direct Vent	Gravity or Induced Flow, Neutral & Negative Pressures Only															
Category	Direct Vent	Direct Vent	Gas Vent			Vent Connector		Chimney Liner		Residential Type & Building Heating Appliance Chimney (RT&BHA)						Chimney Connector	Gas, Oil, Pellet Fueled Appliances	
Model	DT-M	DIRECT-TEMP	RV	OV	R	EFC	DWC	FlexiLiner	VersaLiner	ULTRA-TEMP HT	ULTRA-TEMP	ULTRA-TEMP LD	GALVA-TEMP HT	GALVA-TEMP	GALVA-TEMP LD	DSP	Pellet Pipe, UPP	
Classification	Direct Vent for Multi-Fueled stoves	Direct Vent	Type B	Type B & Type BW	Type B	Single Wall Flex (2 ply)	Double Wall Flex	Single Wall Flex (2 ply)	Single Wall Flex	RT&BHA (Class A) Type HT	RT&BHA (Class A)	RT&BHA (Class A)	RT&BHA (Class A) Type HT	RT&BHA (Class A)	RT&BHA (Class A)	Chimney Connector	Type L	
Maximum Operating Temperature	570° F	Per Appliance Listing	400° F Above Ambient						1000°F Continuous 1400°F 1 Hour 2100°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 2100°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 1700°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 1700°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 2100°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 1700°F 10 Minutes	1000°F Continuous 1400°F 1 Hour 1700°F 10 Minutes	1200°F Continuous 1400°F 1 Hour 2100°F 10 Minutes	570° F	
Appliances & Equipment	Pellets, Corn and Bio-Fuels	Direct Vent Gas Only	Listed gas appliances and other appliances listed for venting with Type B gas vent						WH/UL listed building heating appliances including fireplace stoves.						For use between appliances & chimney.	Pellet fueled, or certain gas, or oil appliances.		
Sizes (ID or Equivalent)	3" x 5" and 4" x 7"	4" Round OD = 6 5/8" and 5" Round OD = 8"	3" – 8" Round OD = ID + 1/2"	4" Oval 5" Oval 5" 1/6" Oval 1/4" Wall	10" – 30" Round OD = ID + 1"	3" – 4"	3" – 5"	3" – 8"	4" – 8"	5", 6", 7" & 8" Round OD = ID + 2"	10", 12" & 14" Round OD = ID + 2"	16", 18", 20", 22" & 24" Round OD = ID + 2"	6" – 8" Round OD = ID + 2"	10", 12" & 14" Round OD = ID + 2"	16", 18", 20", 22" & 24" Round OD = ID + 2"	6", 7" & 8" Round OD = ID + 1/2"	3" & 4" Round OD = ID + 3/4"	
Materials Inner	Al29-4C Stainless Steel	304 Stainless Steel	Aluminum					Aluminum 2-Ply	316 Stainless Steel	304 Stainless Steel	430 Stainless Steel						304 Stainless Steel	
Outer	409 Stainless Steel	Galvanized Steel				N/A	Aluminum	N/A	N/A	430 Stainless Steel			Galvanized Steel			Aluminized Steel	Galvalume Steel	
Insulation	Air	Air	1/4" Air	1/4" Air	NONE	1/4" Air	Available	Available	1" Solid Pack Insulation		1" Solid/Blanket	1" Solid Pack Insulation		1" Solid/Blanket	1/4" Air	3/8" Air		
Combustible Surroundings & Clearances	1"	Refer to Appliance Installation Instructions	Fully enclosable at 1" air space clearance or (for ovals in stud-walls) as determined by factory specified parts.		Fully Enclosable 1"	1" Not to be enclosed		Install In Chimney Only		Fully Enclosable. All sizes require 2" air space clearance to combustibles.						Do Not Enclose Requires 6" air space clearance to combustibles.	Fully Enclosable Requires 1" air space clearance to combustibles.	
Non-Combustible Surroundings & Clearances	Clearances as required for installation, access for inspection or per code.																	
Listing Agency	UL	UL & ITS/WH	Underwriters Laboratories, Inc. (UL)						UL, ITS/WH	Underwriters Laboratories, Inc. (UL)						ITS/WH	UL	
Test Standard	UL641	ANSI/UL	UL441					UL1777		UL 103						UL 103	UL 641	
Codes & References	NFPA - 211	NFPA - 54 NFPA - 211	NFPA -54, NFPA-211						NFPA-211, NFPA-37, NFPA-54						NFPA-211	NFPA-211		

