

2

1

POWER REQUIREMENTS	AC 120 v @ 60Hz		
	BATTERY BACKUP		4X AA+ BATTERY
LAMPS	LED 5v RGB		WS2811 DIODES
	IR REMOTE CONTROLLER		
	CUSTOMIZABLE WIFI APP		
PROFLAME II SYSTEM	5 LEVELS OF FLAME INTENSITY		
	REMOTE CONTROLLED IGNITION		
	VENTED CONFIGURATION ONLY		
GLOWFIRE LOG SPECIES	LDBT-WD72	WESTERN DRIFTWOOD	
HEATING OUTPUT	MAXIMUM HEAT (EN)	95,000 BTU/hr	27.84 kW
	MINIMUM HEAT (EN)	60,000 BTU/hr	17.58 kW
	MAXIMUM HEAT (EP)	75,000 BTU/hr	21.98 kW
	MINIMUM HEAT (EP)	40,000 BTU/hr	11.72 kW

71.75

14.75

LEFT VIEW

POWER OUT

RIGHT VIEW

GAS OUT

6.10

MINIMUM FIRE BOX DIM. (INCHES)		
WIDTH	DEPTH	HEIGHT
72	15	20

1

2

A

B

NOTE:
EN- NATURAL GAS
EP- PROPANE
MUST ADD GLOWFIRE LOGS

TITLE:
BEDROCK TRADITIONAL
LINEAR DROP IN BURNER
LDBT72-EN, LDBT72-EP

SIZE	DWG. NO.	REV
A	LDBT72-XX	B

SCALE: N/A	WEIGHT:	SHEET 1 OF 1
------------	---------	--------------