



On a tous
droit au
design



invicta.fr

PROFESSIONAL
CATALOG

8,99€ - 0320



made in
france

INVICTA

CAST IRON STOVES

KAORI

Stop the cold in its tracks with this charming and discreet stove with proven thermal efficiency. Treat yourself to a warm and cozy Kaori fireplace.

H 740 x W 764 x D 404 mm - Diameter of nozzle 150 mm. Smoke exhaust: Top or Back. (Comparative tables: p145).

Design: B. Daigant.



KAZAN

Kazan is a stylish and high-performance stove inspired by the heat efficiency of cast iron radiators. Its fins provide it with a unique and elegant look, all the while improving its energy efficiency by way of an extended heat transfer surface.

H 768 x W 652 x D 372 mm - Diameter of nozzle 150 mm. Smoke exhaust: Top or Back. (Comparative tables: p145).

Design: B. Daigant.



KAZAN GA

Featuring a screen-printed «grand angle» (GA) pane, our Kazan stove is both powerful and chic. Its fins are designed with an extended heat transfer surface for improved energy efficiency.

H 768 x W 652 x D 372 mm - Diameter of nozzle 150 mm. Smoke exhaust: Top or Back. (Comparative tables: p145).

Design: B. Daigant.



Heating surface	50 to 110 m ²
Optimal Power	9 kW
Consumption	3 kg wood / hour
Power modulation	6 to 13.5 kW
Maximum length of the logs	58 cm
Colour selection	P81844

Heating surface	50 to 110 m ²
Optimal Power	9 kW
Consumption	3 kg wood / hour
Power modulation	6 to 13.5 kW
Maximum length of the logs	58 cm
Colour selection	P81044

Heating surface	50 to 110 m ²
Optimal Power	9 kW
Consumption	3 kg wood / hour
Power modulation	6 to 13.5 kW
Maximum length of the logs	58 cm
Colour selection	P81043

BRADFORD

BRICOL 7208672

ECO LABEL
ECO DESIGN 2022
100% CAST IRON
5 YEARS WARRANTY
POST-CONCEPTION
Hautefort
VERTE
Label du Minis
Label du Minis

Bradford is designed with bold and timeless style. Classic yet trendy, this stove comes in subtle charcoal, elegant enamel ivory, or dazzling enamel red.

H 680 x W 730 x D 579.5 mm - Diameter of nozzle 150 mm. Smoke exhaust: Top or Back. (Comparative tables: p145)

Heating surface	50 to 110 m ²
Optimal Power	9 kW
Consumption	3 kg wood / hour
Power modulation	6 to 13.5 kW
Maximum length of the logs	54 cm
Colour selection	P817244 P817246 P817247

TECHNICAL DATA

					
P613744 CHATEL	P612744 ELTON	P64794X FIFTY ARCHE	P64804X FIFTY on pedestal	P617744 GAYA SLATE	P611844 GAYA LEAF
75	92	80	81	88	89
Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves

DIMENSIONS AND WEIGHT

Height	803	930	733	828	828	1143	1300
Width	476	910	922	922	922	1200	1213
Depth	375	480	442.5	442.5	442.5	503	500.5
Flue diameter	150	180	150	150	150	180	180
Flue height	-	791	-	-	663	-	-
Log length (cm)	34	80	60	60	60	71	71
Weight (kg)	80	210	176.5	180	176.5	206	214

HEATING PERFORMANCE

Optimal heat output (kW) ¹	8	14	10	10	10	12	12
Heat output adjustment ²	5 to 12	9.5 to 21	6.5 to 15	6.5 to 15	6.5 to 15	8 to 18	8 to 18
Efficiency (%) ³	77	75	76	76	76	77	77
CO level (%) ⁴	0.09	0.15	0.08	0.08	0.08	0.1	0.1
Performance rate ⁵	0.4	0.8	0.5	0.5	0.5	0.7	0.7
Flamme verte ⁶ / Ecolabel	7 ★ / A	6 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A

Compatible with BBC RT 2012⁷

Ductable

Eligible for tax credit in France⁸

Autonomy

Extended burning⁹

Heating volume (m³)¹⁰

Heating surface (m²)¹¹

Post combustion system¹²

Adjustable secondary air¹³

Warranty¹⁴

Standard

Finish

TECHNICAL DATA

									
P615844 GOMONT	P611044 ITAYA	P610644 IVAKI	P647844 KAORI	P6104XX KAZAN	P645444 LA BORNE 2	P614544 MAIRY	P918044 MANDOR	P618064 MANDOR	P613644 MESNIL
90	88	72	76	76	70	78	85	85	75
Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves	Cast iron stoves

DIMENSIONS AND WEIGHT

Height	1103	815	850	740	768	684	1071	770	959
Width	550	1051	372	754	652	548	524	852	486.5
Depth	447.5	431	394	404	372	400	426.5	492	385
Flue diameter	150	180	150	150	150	150	150	150	150
Flue height	-	-	718	601	636	-	-	608	-
Log length (cm)	45	71	34	58	58	45	40	66	34
Weight (kg)	128	187	118	152	157 / 162	89	107	144	88

HEATING PERFORMANCE

Optimal heat output (kW) ¹	12	12	7	9	9	7	10	12	8
Heat output adjustment ²	8 to 18	8 to 18	4.5 to 10.5	6 to 13.5	6 to 13.5	4.5 to 10.5	6.5 to 15	8 to 18	5 to 12
Efficiency (%) ³	75	77	78	75	76	78	76	77	77
CO level (%) ⁴	0.10	0.1	0.07	0.10	0.08	0.12	0.09	0.10	0.09
Performance rate ⁵	0.6	0.7	0.4	0.6	0.5	0.5	0.5	0.6	0.4
Flamme verte ⁶ / Ecolabel	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A	7 ★ / A

Compatible with BBC RT 2012⁷

Ductable

Eligible for tax credit in France⁸

Autonomy

Extended burning⁹

Heating volume (m³)¹⁰

Heating surface (m²)¹¹

Post combustion system¹²

Adjustable secondary air¹³

Warranty¹⁴

Standard

Finish

